

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture	HASLE GUN39A
Registration number	-
Synonyms	None.
Issue date	14-November-2018
Version number	01
Revision date	-
Supersedes date	-

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Industrial use.
Uses advised against	Workers (and your customers or users in the case of resale) should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.

1.3. Details of the supplier of the safety data sheet

Company name	HASLE Refractories A/S
Address	Kanegaardsvej 1 3700 Roenne Denmark
Telephone	+45 56 95 18 00
Contact person	HASLE Product Manager
E-mail	hasle@hasle-refractories.com
Website	www.hasle-refractories.dk

1.4. Emergency telephone number	+45 56 95 18 00
---------------------------------	-----------------

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards		
Specific target organ toxicity - repeated exposure	Category 1 (Lung)	H372 - Causes damage to organs (Lung) through prolonged or repeated exposure.

Hazard summary	Causes damage to organs through prolonged or repeated exposure. Exposure to powder or dusts may be irritating to eyes, nose and throat. Prolonged exposure may cause chronic effects. Occupational exposure to the substance or mixture may cause adverse health effects.
-----------------------	---

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Cristobalite, Quartz

Hazard pictograms



Signal word: Danger

Hazard statements

H372 Causes damage to organs (Lung) through prolonged or repeated exposure.

Precautionary statements

Prevention

P260 Do not breathe dust.
P264 Wash thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.

Response

P314 Get medical advice/attention if you feel unwell.

Storage

Store away from incompatible materials.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information None.

2.3. Other hazards This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Mullite	20 - 50	1302-93-8 215-113-2	-	-	
Classification:	-				
Amorphous Silica (glass)	15 - 25	7631-86-9 231-545-4	-	-	
Classification:	-				
Cristobalite	10 - 15	14464-46-1 238-455-4	-	-	#
Classification:	STOT RE 1;H372				
Quartz	1 - < 10	14808-60-7 238-878-4	-	-	#
Classification:	STOT RE 1;H372				
Aluminium oxide	0 - 10	1344-28-1 215-691-6	01-2119529248-35-xxxx	-	
Classification:	-				
Silicon Dioxide powder	0 - 10	69012-64-2 231-545-4	-	-	
Classification:	-				
Calcium Aluminate	1 - 5	65997-16-2 266-045-5	-	-	
Classification:	Eye Irrit. 2;H319				

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

4.1. Description of first aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Do not rub eyes. Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and delayed Dusts may irritate the respiratory tract, skin and eyes. Coughing. Prolonged exposure may cause chronic effects.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards	No unusual fire or explosion hazards noted.
5.1. Extinguishing media	
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
5.2. Special hazards arising from the substance or mixture	None known.
5.3. Advice for firefighters	
Special protective equipment for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Special fire fighting procedures	Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe dust. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.
For emergency responders	Use personal protection recommended in Section 8 of the SDS.
6.2. Environmental precautions	Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
6.3. Methods and material for containment and cleaning up	Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Collect dust using a vacuum cleaner equipped with HEPA filter. Stop the flow of material, if this is without risk. Large Spills: Wet down with water and dike for later disposal. Shovel the material into waste container. Following product recovery, flush area with water. Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal. Never return spills to original containers for re-use.
6.4. Reference to other sections	For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling	Minimise dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
7.2. Conditions for safe storage, including any incompatibilities	Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see section 10 of the SDS).
7.3. Specific end use(s)	Industrial use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value	Form
Aluminium oxide (CAS 1344-28-1)	TWA	4 mg/m ³	Respirable dust.
		10 mg/m ³	Inhalable dust.
Amorphous Silica (glass) (CAS 7631-86-9)	TWA	6 mg/m ³	Inhalable dust.
		2.4 mg/m ³	Respirable dust.
Cristobalite (CAS 14464-46-1)	TWA	1 fibers/ml	Fiber.
		5 mg/m ³	Fiber.
Dust	TWA	0.1 mg/m ³	Respirable.
		4 mg/m ³	Respirable dust.

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value	Form
Mullite (CAS 1302-93-8)	TWA	10 mg/m ³	Inhalable dust.
		4 mg/m ³	Respirable dust.
Quartz (CAS 14808-60-7)	TWA	10 mg/m ³	Inhalable dust.
		0.1 mg/m ³	Respirable.
Silicon Dioxide powder (CAS 69012-64-2)	TWA	6 mg/m ³	Inhalable dust.
		2.4 mg/m ³	Respirable dust.

EU. OELs, Directive 2004/37/EC on carcinogen and mutagens from Annex III, Part A

Components	Type	Value	Form
Cristobalite (CAS 14464-46-1)	TWA	0.1 mg/m ³	Respirable fraction and dust
Quartz (CAS 14808-60-7)	TWA	0.1 mg/m ³	Respirable fraction and dust

Biological limit values No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures Follow standard monitoring procedures.

Derived no effect levels (DNELs)**General Population**

Components	Value	Assessment factor	Notes
Aluminium oxide (CAS 1344-28-1) Long-term, Systemic, Oral	6.58 mg/kg bw/day	20	Repeated dose toxicity

Workers

Components	Value	Assessment factor	Notes
Aluminium oxide (CAS 1344-28-1) Long-term, Local, Inhalation	15.63 mg/m ³	3	Repeated dose toxicity
Long-term, Systemic, Inhalation	15.63 mg/m ³	3	Repeated dose toxicity

Predicted no effect concentrations (PNECs) Not available.

Exposure guidelines Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.

8.2. Exposure controls

Appropriate engineering controls Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If engineering measures are not sufficient to maintain concentrations of dust particulates below the OEL (occupational exposure limit), suitable respiratory protection must be worn. If material is ground, cut, or used in any operation which may generate dusts, use appropriate local exhaust ventilation to keep exposures below the recommended exposure limits.

Individual protection measures, such as personal protective equipment

General information	Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.
Eye/face protection	Wear safety glasses with side shields (or goggles). Eye protection should meet standard EN 166.
Skin protection	
- Hand protection	Wear appropriate chemical resistant gloves. Wear suitable gloves tested to EN374.
- Other	Wear suitable protective clothing.
Respiratory protection	In case of inadequate ventilation or risk of inhalation of dust, use suitable respiratory equipment with particle filter (type P2). Particle filter with medium efficiency for solid and liquid particles (eg. As EN 143 or 149, Type P2 or FFP2).
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.

Hygiene measures Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Environmental exposure controls Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state	Solid.
Form	Powder.
Colour	Grey.
Odour	Odourless.
Odour threshold	Not applicable.
pH	Not applicable.
Melting point/freezing point	> 1000 °C (> 1832 °F)
Initial boiling point and boiling range	Not applicable.
Flash point	Not applicable.
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not applicable.
Flammability limit - upper (%)	Not applicable.
Vapour pressure	Not applicable.
Vapour density	Not applicable.
Relative density	Not available.
Solubility(ies)	No data available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not applicable.
Decomposition temperature	Not available.
Viscosity	Not applicable.
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.

9.2. Other information

Density	0.20 - 3.00 g/cm ³
---------	-------------------------------

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Contact with incompatible materials.
10.5. Incompatible materials	Strong oxidising agents.
10.6. Hazardous decomposition products	Carbon oxides. Aluminum oxides. Silicon oxides.

SECTION 11: Toxicological information

General information	Occupational exposure to the substance or mixture may cause adverse effects.
---------------------	--

Information on likely routes of exposure

Inhalation	Dust may irritate respiratory system. Prolonged inhalation may be harmful.
Skin contact	Dust or powder may irritate the skin.
Eye contact	Dust may irritate the eyes.
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.

Symptoms	Dusts may irritate the respiratory tract, skin and eyes. Coughing.
----------	--

11.1. Information on toxicological effects

Acute toxicity	May cause discomfort if swallowed.
----------------	------------------------------------

Components	Species	Test Results
Amorphous Silica (glass) (CAS 7631-86-9)		
Acute		
Dermal		
LD50	Rabbit	> 5000 mg/kg, 24 Hours
Inhalation		
<i>Dust</i>		
LC50	Rat	> 0.14 mg/l, 4 Hours
Oral		
LD50	Rat	> 3300 mg/kg
Skin corrosion/irritation	Dust or powder may irritate the skin.	
Serious eye damage/eye irritation	Dust may irritate the eyes.	
Respiratory sensitisation	Due to partial or complete lack of data the classification is not possible.	
Skin sensitisation	Due to partial or complete lack of data the classification is not possible.	
Germ cell mutagenicity	Due to partial or complete lack of data the classification is not possible.	
Carcinogenicity	<p>In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled. Risk of cancer cannot be excluded with prolonged exposure.</p>	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Amorphous Silica (glass) (CAS 7631-86-9)	3 Not classifiable as to carcinogenicity to humans.	
Cristobalite (CAS 14464-46-1)	1 Carcinogenic to humans.	
Quartz (CAS 14808-60-7)	1 Carcinogenic to humans.	
Silicon Dioxide powder (CAS 69012-64-2)	3 Not classifiable as to carcinogenicity to humans.	
Reproductive toxicity	Due to partial or complete lack of data the classification is not possible.	
Specific target organ toxicity - single exposure	Due to partial or complete lack of data the classification is not possible.	
Specific target organ toxicity - repeated exposure	Causes damage to organs (Lung) through prolonged or repeated exposure.	
Aspiration hazard	Due to partial or complete lack of data the classification is not possible.	
Mixture versus substance information	No data available.	
Other information	Crystalline silica: Overexposure to the respirable dust of crystalline silica (quartz or cristobalite, less than or equal to 5 microns in size) may lead to silicosis in humans, which is a progressive and irreversible lung disease.	

SECTION 12: Ecological information

12.1. Toxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
12.2. Persistence and degradability	Not applicable to inorganic substances.
12.3. Bioaccumulative potential	The product is not expected to bioaccumulate.
Partition coefficient n-octanol/water (log Kow)	Not available.
Bioconcentration factor (BCF)	Not available.
12.4. Mobility in soil	No data available.
12.5. Results of PBT and vPvB assessment	This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.

12.6. Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

EU waste code The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Disposal methods/information Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 14: Transport information

ADR

14.1. - 14.6.: Not regulated as dangerous goods.

RID

14.1. - 14.6.: Not regulated as dangerous goods.

ADN

14.1. - 14.6.: Not regulated as dangerous goods.

IATA

14.1. - 14.6.: Not regulated as dangerous goods.

IMDG

14.1. - 14.6.: Not regulated as dangerous goods.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Aluminium oxide (CAS 1344-28-1)

Mullite (CAS 1302-93-8)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorisation, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed.

Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

National regulations

Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended. Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

LD50: Lethal Dose, 50%.

LC50: Lethal Concentration, 50%.

References

HSDB® - Hazardous Substances Data Bank

Registry of Toxic Effects of Chemical Substances (RTECS)

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any H-statements not written out in full under Sections 2 to 15

H319 Causes serious eye irritation.

H372 Causes damage to organs through prolonged or repeated exposure by inhalation.

H372 Causes damage to organs through prolonged or repeated exposure.

Training information

Follow training instructions when handling this material.

Disclaimer

HASLE Refractories A/S cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.